



Deines Model 1848 OHV

Tractor Specifications



Engine

Kohler Command 18HP, CH620-3039
Overhead Valve Design
Hydraulic Valve Lifters
Electronic Ignition
Dual Element Air Cleaner
Closed Breather System
Full Pressure Lubrication
Large Capacity In-Line Fuel Filter
Full Flow Oil Filter
Dual Oil Drain
Variable-Speed Governor
Fuel Shutdown Solenoid
Self-relieving Smart-Choke Carburetor
Pulse Fuel Pump
12-Volt Shift Starter
20 Amp Alternator

Rear Tire Size

2-Ply, Pneumatic 15-6:00 x 6, Tubeless Tires

Steering

2 Levers, One For Each Wheel

Engaging System

Electric Clutch

Deck Lift

Manual Deck Lift

Net Weight

725 Pounds

Height

41.5 Inches

Hydrostatic Transmission

Eaton Model 6, 2 Per Machine
Chain Reduction System
Turning Radius Zero Degree Right & Left
Speeds Infinite Variation From 0-7 MPH

Length

68 Inches

Width

43.5 Inches

Fuel Tank

5 Gallon Capacity, EPA Approved with
Evaporative Emission Port Connected to EPA
Approved Carbon Canister.

Options

Dual Tail Wheel Assembly
Deluxe Seat, with High Back and Arm Rests
Seat Suspension For Standard Seat
Electric Lift
Snow-blower
Snow Removal Blade
Vacuum Collectors

Wheels

8" Disc Type

Drive Tires

2-Ply, Pneumatic 18-8:50 x 8 Turf Saver Tires,

Deck Specifications

Deck Material

11 Gauge Steel

Front Gauge Wheel

2 Each, Pneumatic 11-4:00 x 5, 2 Ply Rib
Tubeless

Spindle Housing

Heavy Duty Ductile Iron

Width of Cut

47 Inches

Blades & Material

2 Each, 23.75" x 2" x .25"
Heat Treated, Passes 90 Degree Bend Test

Width With Grass Chute

57 Inches

Rear Deck Gauge Rollers

2 Each, 3" Diameter x 7" Hard Plastic

Cutting Deck Weight

265 Lbs.

Cutting Adjustment

1" - 4", Set by Adjustable Gauge Wheels
& Rear Gauge Rollers

Optional Equipment

Vacuum Collectors
Gator Blades

Spindle Shafts

2 Each, 1" Ground & Polished Stress proof

Gear Box

Superior, Heavy Duty, 90 Degree Gear
1:1.1 Ratio Double Bearing



Deines
Manufacturing
Corporation

Home Office:
P.O. Box 737
Hays, KS 67601

1-800-624-6774

Plant:
306 W. Hwy. 4
Ransom, KS 67572

785-731-2271

www.marty-j.com